

CLICK WOOD / CLASSIC



ISOCORE 6.5 / IC725110

CALHOUN OAK



ISOCORE 6.5 / IC978102

AMSTERDAM OAK WHITE

Featuring  **ISOCORE** Technology™



ISOCORE 6.5 / IC978108

AMSTERDAM OAK GREY

CLICK WOOD / CLASSIC



ISOCORE 6.5 / IC725110

CALHOUN OAK



ISOCORE 6.5 / IC978102

AMSTERDAM OAK WHITE









ISOCORE 6.5 / IC978108

AMSTERDAM OAK GREY

CLICK WOOD / CLASSIC

CONSTRUCTION / CONSTRUCTION / COSTRUZIONE / CONSTRUCTIE	
THICKNESS / EPAISSEUR TOTALE / SPESSORE / TOTALE DIKTE	
WEAR LAYER / COUCHE D'USURE / STRATO D'USURA / SLIJTLAAG	
UTILIZATION CLASS / CLASSE D'USAGE / CLASSE D'UTILIZZO / GEBRUIKERSKLASSE	
COATING / PROTECTION / RIVESTIMENTO / BESCHERMING	
EMBOSSING / STRUCTURE / STRUTTURA / STRUCTUUR	
BEVELLED / BISEAUTÉ / BISELLATURA / V-GROEF	
PLANK SIZE / DIMENSIONS DE LA LAME / DIMENSIONI / AFMETING PER PANEEL	
CARTON PACKING / EMBALLAGES EN CARTON / SCATOLE / KARTONNEN VERPAKKING	
PALLET PACKING / BOÎTES PAR PALETTE / NR SCATOLE À PALETTA / DOZEN PER PALLET	
NET-GROSS WEIGHT PER PALLET / POIDS NET-BRUT PAR PALETTE / PESO NETTO - LORDO À PALETTA / GEWICHT NETTO - BRUTO PER PALLET	
IMPACT SOUND INSULATION / ISOLATION ACOUSTIQUE / ISOLAMENTO ACUSTICO / GELUIDSREDUCTIE	ISO 717-2
CASTO CHAIR RESISTANCE / ESSAI DE LA CHAISE À ROULETTES / PROVA CON POLTRONA A ROTELLE / ROLWEERSTAND BUREAUSTOEL	EN ISO 4918 - EN 425
EFFECT OF FURNITURE LEG / EFFECT DE PIED DE MEUBLE / EFFETTO DI GAMBE MOBILI / EFFECT VAN MEUBILAIR POTEN	EN 424
THERMAL RESISTANCE / RÉSISTANCE THERMIQUE / RESISTENZA TERMICA / THERMISCHE WEERSTAND	EN ISO 12524
ELECTROSTATIC PERFORMANCE / POTENTIEL DE CHARGE ELECTROSTATIQUE / POTENZIALE DI CARICA ELETTROSTATICA / ELEKTROSTATISCHE EIGENSCHAPPEN	EN 1815
SLIP RESISTANCE / ANTIDÉPARANT / RESISTENZA ALLO SCIVOLAMENTO / SLIPWEERSTAND	DIN 51130
WEAR RESISTANCE / RÉSISTANCE D'USURE / RESISTANCE ALL'USURA / SLIJTVASTHEID	EN 660-2
IMPACT RESISTANCE / RESISTANCE AUX CHOCS / RESISTENZA ALL'URTO / SLAGVASTHEID	EN 13329+A1
LOCKING STRENGTH / FORCE DE VERROUILLAGE / FORZA DI BLOCCAGGIO / CLICKVASTHEID	ISO 24334
RESIDUAL INDENTATION / POINÇONNEMENT RÉMANENT / SENSIBILITÀ DI IMPRESSIONE / INDRUKGEVOELIGHEID	EN ISO 24343-1
DIMENSIONAL STABILITY / STABILITÉ DIMENSIONNELLE / STABILITÀ DIMENSIONALE / DIMENSIONALE STABILITEIT	EN 434
FIRE RATING / CLASSIFICATION AU FEU / CLASSIFICAZIONE AL FUOCO / BRANDKLASSE	EN ISO 9239-1
FORMALDEHYDE EMISSION / EMISSION DE FORMALDEHYDE / EMISSIONE DI FORMALDEIDE / FORMALDEHYDE EMISSIE	
WARRANTY FOR DOMESTIC USE / PÉRIODE DE GARANTIE USAGE DOMESTIQUE / GARANZIA PER USO DOMESTICO / GARANTIEPERIODE HUISHOUELIJK GEBRUIK	
WARRANTY FOR COMMERCIAL USE / PÉRIODE DE GARANTIE USAGE COMMERCIAL / GARANZIA PER USO COMMERCIALE / GARANTIEPERIODE COMMERCIEEL GEBRUIK	

	CLICK WOOD CLASSIC ISOCORE 6.5
	1.5 MM LVT + 4 MM ISOCORE + 1 MM IXPE PAD
	6.5 MM
	0.55 MM
	CLASSE 33 CLASSE 42
	PU WITH CERAMIC BEAD - ULTRAFRESH
	TRU-WOOD
	YES
	190 X 1210 MM
	1.84 M ² 8 PLANKS
	40 PACKS / 73.6 M ² / PALLET
	532 KG / 542 KG
	21 DB
	NO DAMAGE
	NO DAMAGE
	0.0621 M ² K/W
	2.0 KV
	PASSES GRADE R10
	> 4000 cycles
	1450 MM
	LONG SIDE - 1.32 KN/M SHORT SIDE - 2.23 KN/M
	< 0.20 MM
	0.10 %
	BFL-S1
	CLASS E1
	25 YEARS
	10 YEARS